
ELIPSE® HALF-FACE MASK +HESPA[™] A1P3 DUST (R) Filters

FILTER TECHNOLOGY





Inhalation valve



Efficiency

At 1000 ppm:

P3 >99,95% for 0,3 µm particulate

A1 >70 minutes cyclohexane ($C_{s}H_{12}$)

Standards

EN140: 1998 Mask Body EN14387: 2004 + A1: 2008 A1P3 R D (suited for organic gases and dust) CE 2797

Weight

Mask + Filter: net (S/M) 267 g; (M/L) 271 g gross (S/M) 337 g; (M/L) 341 g Filter: net 90 g each; both net 180 g, gross 208 g

Shelf Live

3 years (mask & filters) See storage conditions on Instructions for Use. Filters are re-usable and changeable.

Material

- Mask: Medical grade TPE Conforms to ISO 10993-10: 2010 for irritations. Mask body latex and silicone free, odour free. Valve Body in Nylon, Inhalation/Exhalation diaphragm in Silicone. 4 point adjustable elasticated head and neck strap with comfort pad in TPE. • Gas Filters: Activated carbon sealed into a ABS Shell.

• Particulate filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated. Particulate filters are integrated permanently with the carbon element.

Production

United Kingdom 100% of filters NaCl Tested

	Code	Description	Quantity
B	SPR338 (S/M) SPR503 (M/L)	Elipse Half Mask complete with A1P3 filters	10 pcs. per box
	SPR341	Elipse A1P3 replacement filters	10 sets of 2 pcs. per box
95	SPM008	Elipse Low Profile Mask Carry Case (Belt holder)	10 sets per box
C.	SPM414	Portacount Face Fit Kit adaptor	10 sets per box
	SPM420	Kit of Prefilter Kits - 2 holder and 10 pads	10 kits per box
	SPM421	Kit of Prefilter - 20 pads	10 kits per box

Applications - Organic gases, dust, mist and fumes



confined space (gas welding) Manufacturing

Metal Fumes and Dust in

Weldina



Construction Paint, Moulds.

Agriculture



Car & Ship Repair

Epoxite, Paint, Solvants



Pesticides

GVS Filter Technology UK NFC House - Vickers Industrial Estate - Mellishaw Lane, Morecambe Lancashire LA3 3EN - tel. +44 (0) 1524 847600 - gvsuk@gvs.com www.gvs.com

